



## NEW STAINLESS STEEL!!!

The Ultimate Stainless steel clamp has arrived. Constructed from a 316 marine grade stainless steel these clamps have exceeded every expectation in a quality finish. Coming in a high Polish or Satin finish these are certain to impress any client ... Carefully engineered and certified for any core drilling or deck mounting job up to glass widths of 1800mm\*\*. With the glass not touching the ground, drainage is maximized.

### SPECIFICATIONS

INFORMATION	CORE DRILLED SPIGOT	BASE PLATED SPIGOT
<b>Material</b>	316 Stainless Steel	316 Stainless Steel
<b>Length</b>	245mm	180mm
<b>Post Width</b>	50mm	50mm
<b>Base Width</b>	50mm	125mm
<b>Distance Between Glass Cross Bolts</b>	68mm Centre to Centre	68mm Centre to Centre
<b>Height Adjustment Bolt</b>	M16	Nil (packers available)
<b>Tilt Adjustment Available</b>	Yes	Yes
<b>Dress Ring</b>	Included	Included – Domical Cover

### ADVANTAGES

#### Core Drilled

- Fully adjustable to ensure precision and accuracy throughout the job
- Height of spigot can be altered with adjustment bolt
- Packers available in kit to ensure secure fit.
- Tilt adjustment of glass possible
- Can be embedded in slab for stability
- Designed for easy removal and replacement of glass

#### Base Plated

- Can be bolted to decking
- Flexibility of positioning
- Also fully adjustable to ensure precision and accuracy throughout the job
- Packers available in kit to ensure secure fit
- Tilt adjustment of glass possible
- Designed for easy removal and replacement of glass
- 1mm & 3mm bottom packers available for minor height adjustments

\*\* Engineer recommendation is that 15mm thick glass be used for spans over 1800mm, however please note that 15mm thick glass is not compatible with the Glass Outlet spigot.